

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 62-216803  
(43)Date of publication of application : 24. 09. 1987

(51)Int. CI. B60C 19/00


(21)Application number : 61-058915 (71)Applicant : BRIDGESTONE CORP  
(22)Date of filing : 17. 03. 1986 (72)Inventor : FUKUSHIMA HIROSHIGE  
TAKAYAMA MASAHIRO  
GOSHIMA MICHIO

(54) TYRE RESONANCE PREVENTING MATERIAL

(57)Abstract:

PURPOSE: To prevent the generation of resonance noise occasioned by running and to reduce the generation of noise, by a method wherein an annular porous material having a specified apparent volume and apparent density is built in the inner pressure air-filled cavity of a tyre.

CONSTITUTION: An annular tyre resonance preventing material 3, formed by a porous material having an apparent volume of from 25% or more to 70% of less of the total inner volume of an inner pressure air-filled cavity 4 under inflation of a tyre 1 and apparent density of 0.1gw/cm<sup>2</sup> or less, is located in the inner pressure air-filled cavity 4 formed between the inner surface of the tyre 1 and the outer surface of a rim 2. This constitution enables reduction of the peak of the power value of load noise during load-rolling of the tyre, and allows reduction of the generation of noise.



LEGAL STATUS

[Date of request for examination]  
[Date of sending the examiner's decision of rejection]  
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]  
[Date of final disposal for application]  
[Patent number]  
[Date of registration]

4  
[Number of appeal against examiner's  
decision of rejection]

[Date of requesting appeal against  
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office